

INDUSTRIAL COMPONENT DATA

ZEC 1,0/ 4-LPV-3,5 C1 1915673 PHOENIX CONTACT PCB connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZEC 1,0/ 4-LPV-3,5 C1



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZEC 1,0/ 4-LPV-3,5 C1
Catalog number	1915673
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-80D98B6FF5
Generated	2026-08-03

Product Overview

PCB connector

Connector for printed circuit board, nominal section: 1 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 200 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: ZEC 1.0/. -LPV, pitch: 3.5 mm, mounting: Direct plug-in connection technology, driver/printed circuit board connection direction: 0 °, number of solder pins per potential: 2, plug-in system: ZEC, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1915673

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 365 (C-1-2013)

GTIN 4017918181505

Weight per Piece (excluding packing) 2.680 g

Custom tariff number 85366930

Country of origin GR (Greece)

Dimensions

Length 22.9 mm

Height 7 mm

Width 15.4 mm

Pitch 3.5 mm

Dimension a 14 mm

General

Range of articles ZEC 1,0/...-LPV

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/2) 200 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal voltage UN 160 V

Nominal cross section 1 mm²

Maximum load current 8 A

Insulating material PA

Flammability rating according to UL 94 V0

Number of positions 4

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1915673 Connectors (EC002637)

Feature Name

Feature Value

Contact type (EF001587)

Bus

Number of poles (EF001391)

4

Number of plu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZEC 1,0/ 4-LPV-3,5 C1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.