INDUSTRIAL COMPONENT DATA

SPT-THR 1,5/ 9-V-5,08 P20 R88 1823599 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT-THR 1,5/ 9-V-5,08 P20 R88

Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT-THR 1,5/ 9-V-5,08 P20 R88
Catalog number	1823599
Category	Printed circuit board terminal
Minimum order	200 Pcs
Document ID	EO-70B71B8584
Generated	2026-08-03

Product Overview

PCB terminal block
Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 320 V, nominal section: 1.5 mm², number of potentials: 9, number of rows: 1, number of poles per row: 9, family of articles: SPT 1.5/.. -V-THR, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Weld THR, conductor connection direction/printed circuit board: 90°, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 2 mm, number of solder pins per potential: 2, packaging type: 88 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1823599
Packing unit 200 pc
Minimum order quantity 200 pc
Note Made to Order (non-returnable)
Catalog page Page 13 (NTK-2014)
GTIN 4046356815413
Weight per Piece (excluding packing) 8.000 g
Custom tariff number 85369010
Country of origin DE (Germany)

Dimensions
Length [l] 7.7 mm
Pitch 5.08 mm
Dimension a 40.64 mm
Width [w] 44.64 mm
Height 13.6 mm
Height [h] 15.6 mm
Solder pin [P] 2 mm
Pin spacing 5.5 mm
Hole diameter 1.1 mm
General
Range of articles SPT 1,5/..-V-THR
Insulating material group IIIa
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 250 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 500 V
Nominal current IN 13.5 A
Nominal cross section 1.5 mm²
Insulating material LCP
Solder pin surface
Flammability rating according to UL 94 V0
Stripping length 8 mm
Number of positions 9
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.2 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.2 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 16
Sta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT-THR 1,5/ 9-V-5,08 P20 R88 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.