

INDUSTRIAL COMPONENT DATA

SPTA 5/ 2-7,5-ZB 1819082 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTA 5/ 2-7,5-ZB



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTA 5/ 2-7,5-ZB
Catalog number	1819082
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-4A3DD11D57
Generated	2026-08-01

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 41 A, nominal voltage (III/2): 1000 V, nominal cross-section: 6 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: SPTA 5/, pitch: 7.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 60 °, color: green, Pin arrangement: Zigzag Pins W, Pin length [P]: 4.6 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1819082

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 25 (NTK-2014)

GTIN 4046356787192

Weight per Piece (excluding packing) 11.380 g

Custom tariff number 85369010

Country of origin IN (India)

Item properties

Brief article description PCB terminal block

Range of articles SPTA 5/
Pitch 7.5 mm
Number of positions 2
Connection method Push-in spring connection
Mounting type Wave soldering
Pin layout linear double pinning
Number of levels 1
Number of connections 2
Number of potentials 2
Electrical parameters
Rated current 41 A
Rated insulation voltage (III/2) 1000 V
Rated surge voltage (III/2) 8 kV
Connection capacity
Conductor cross section solid 0.2 mm² ... 6 mm²
Conductor cross section flexible 0.2 mm² ... 6 mm²
Conductor cross section AWG / kcmil 24 ... 8
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 6 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 4 mm²
2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.25 mm² ... 1.5 mm²
Stripping length 15 mm
Material data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Metal surface terminal point (top layer) Tin (10 - 16 µm Sn)
Metal surface soldering area (top layer) Tin (10 - 16 µm Sn)
Material data - housing
Insulating material PA
Insulating material group I
CTI according to IEC 60112 600
Flammab...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTA 5/ 2-7,5-ZB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.