

INDUSTRIAL COMPONENT DATA

FFKDSA/V2-7,62 1790377 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: FFKDSA/V2-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	FFKDSA/V2-7,62
Catalog number	1790377
Category	Printed circuit board terminal
Minimum order	250 Pcs
Document ID	EO-32040CDA53
Generated	2026-07-31

Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 17.5 A, rated voltage (III/2): 630 V, rated cross-section: 1.5 mm², number of potentials: 1, number of rows: 1, number of poles per row: 1, article family: FFKDS(A)/V2, pitch: 7.62 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 90 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.4 mm, number of solder pins per potential: 2, packaging type: boxed packaging. Individual disc for the individual composition of different numbers of poles. To complete the block, an additional terminal block is required (see accessories). Block-bound items in different numbers of poles are also available.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1790377

Packing unit 250 pc

Catalog page Page 151 (C-1-2013)

GTIN 4017918044282

Weight per Piece (excluding packing) 1.170 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [l] 10 mm

Pitch 7.62 mm

Width [w] 7.62 mm

Height 16 mm

Height [h] 19.4 mm

Solder pin [P] 3.4 mm

Hole diameter 1.3 mm

General

Range of articles FFKDS(A)/V2

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 500 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current I_N 17.5 ANominal cross section 1.5 mm²Maximum load current 17.5 A (with 1.5 mm² conductor cross section)

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 10 mm

Number of positions 1

Connection dataConductor cross section solid min. 0.2 mm²Conductor cross section solid max. 1.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 1.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 0.75 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Standar...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FFKDSA/V2-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.