


INDUSTRIAL COMPONENT DATA

FRONT 2,5-H/SA 5/ 7 1988257 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: FRONT 2,5-H/SA 5/ 7



Manufacturer	PHOENIX CONTACT
MPN / Reference	FRONT 2,5-H/SA 5/ 7
Catalog number	1988257
Category	Printed circuit board terminal
Minimum order	20 Pcs
Document ID	EO-EDDED4F8D2
Generated	2026-08-01

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 400 V, nominal section: 2.5 mm², number of potentials: 7, number of rows: 1, number of poles per row: 7, article family: FRONT 2.5-H/SA 5, pitch: 5 mm, connection type: Front screw connection, mounting: Wave soldering, Conductor/PCB connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 2, packaging type: boxed. The item can be aligned with different numbers of poles!

Printed circuit board terminal, nominal current: 24 A, rated voltage (III/2): 400 V, nominal cross section: 2.5 mm², number of potentials: 7, number of rows: 1, number of positions per row: 7, product range: FRONT 2,5-H/SA 5, pitch: 5 mm, connection method: Front screw connection, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, number of solder pins per potential: 2, type of packaging: packed in cardboard. The article can be aligned to create different nos. of positions!

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family FRONT 2,5-H/SA 5

Product line COMBICON Terminals M

Type PC terminal block can be aligned

Number of positions 7

Pitch 5 mm
Number of connections 7
Number of rows 1
Number of potentials 7
Pin layout Linear pinning
Solder pins per potential 2
Data management status
Article revision 06
Electrical propertiesNominal current I_N 24 A
Nominal voltage U_N 400 V
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 400 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
Connection dataConnection technology
Type PC terminal block can be aligned
Nominal cross section 2.5 mm²
Conductor connection
Connection method Front screw connection
Conductor cross section rigid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 14
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 1.5 mm²
2 conductors with same cross section, solid 0.2 mm² ... 0.75 mm²
2 conductors with same cross section, flexible 0.2 mm² ... 0.75 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 0.34 mm²
Stripping length 9 mm
Drive form screw head Slotted
Tightening torque 0.4 Nm ... 0.5 Nm
MountingMounting type Wave soldering
Pin layout Linear pin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FRONT 2,5-H/SA 5/ 7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.