

INDUSTRIAL COMPONENT DATA

FRONT 2,5-H/SA10/12 1773251 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: FRONT 2,5-H/SA10/12



Manufacturer	PHOENIX CONTACT
MPN / Reference	FRONT 2,5-H/SA10/12
Catalog number	1773251
Category	Printed circuit board terminal
Minimum order	20 Pcs
Document ID	EO-97AC60C160
Generated	2026-08-03

Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 24 A, rated voltage (III/2): 400 V, rated cross-section: 2.5 mm², number of potentials: 12, number of rows: 1, number of poles per row: 12, article family: FRONT 2.5-H/SA10, pitch: 5 mm, connection type: Front screw connection, mounting: Wave soldering, driver/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 5 mm, number of solder pins per potential: 2, packaging type: boxed packaging. The item can be aligned with different numbers of poles!

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1773251

Packing unit 20 pc

Note Made to Order (non-returnable)

Catalog page Page 115 (C-1-2013)

GTIN 4046356465809

Weight per Piece (excluding packing) 43.350 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [l] 18.5 mm

Pitch 5 mm

Dimension a 55 mm

Width [w] 62.5 mm

Height 18.5 mm

Height [h] 22.7 mm

Solder pin [P] 4.2 mm

Pin spacing 10 mm

Hole diameter 1.2 mm

General

Range of articles FRONT 2,5-H/SA10

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 24 A

Nominal cross section 2.5 mm²

Maximum load current 17.5 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 9 mm

Number of positions 12

Screw thread M2,5

Tightening torque, min 0.4 Nm

Tightening torque max 0.5 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross sec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FRONT 2,5-H/SA10/12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.