


**INDUSTRIAL COMPONENT DATA**

# MKDS 1/ 9-3,81 SMD BK 1727298 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 1/ 9-3,81 SMD BK



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | MKDS 1/ 9-3,81 SMD BK          |
| Catalog number  | 1727298                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 12 Pcs                         |
| Document ID     | EO-007A812067                  |
| Generated       | 2026-08-02                     |

## Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 8 A, nominal voltage (III/2): 160 V, nominal section: 1 mm<sup>2</sup>, number of potentials: 9, number of rows: 1, number of poles per row: 9, family of articles: MKDS 1/..-SMD, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, mounting: SMD soldering, conductor/printed circuit board connection direction: 0 °, color: black, Pin arrangement: Linear pin arrangement, number of solder pins per potential: 1, packaging type: Bar loader

Printed circuit board terminal, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1 mm<sup>2</sup>, number of potentials: 9, number of rows: 1, number of positions per row: 9, product range: MKDS 1/..-SMD, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, mounting: SMD soldering, conductor/PCB connection direction: 0 °, color: black, Pin layout: Linear pad geometry, number of solder pins per potential: 1, type of packaging: Tube magazine

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

## Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family MKDS 1/..-SMD

Product line COMBICON Terminals S

Type PC termination block

Number of positions 9

Pitch 3.81 mm  
Number of connections 9  
Number of rows 1  
Number of potentials 9  
Pin layout Linear pad geometry  
Solder pins per potential 1  
Data management status  
Article revision 06  
Electrical propertiesNominal current  $I_N$  8 A  
Nominal voltage  $U_N$  160 V  
Rated voltage (III/3) 160 V  
Rated surge voltage (III/3) 2.5 kV  
Rated voltage (III/2) 160 V  
Rated surge voltage (III/2) 2.5 kV  
Rated voltage (II/2) 250 V  
Rated surge voltage (II/2) 2.5 kV  
Connection dataConnection technology  
Type PC termination block  
Nominal cross section 1 mm<sup>2</sup>  
Conductor connection  
Connection method Screw connection with tension sleeve  
Conductor cross section rigid 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section flexible 0.14 mm<sup>2</sup> ... 1 mm<sup>2</sup>  
Conductor cross section AWG 26 ... 16  
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 0.5 mm<sup>2</sup>  
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm<sup>2</sup> ... 0.5 mm<sup>2</sup>  
2 conductors with same cross section, solid 0.14 mm<sup>2</sup> ... 0.5 mm<sup>2</sup>  
2 conductors with same cross section, flexible 0.14 mm<sup>2</sup> ... 0.2 mm<sup>2</sup>  
Stripping length 5 mm  
Drive form screw head Slotted (L)  
Tightening torque 0.22 Nm ... 0.25 Nm  
MountingMounting type SMD soldering  
Pin layout Linear pad geometry  
Material specificationsMaterial data - contact  
Note WEEE/RoHS-compliant, free of whiskers acc...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 1/ 9-3,81 SMD BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.