

INDUSTRIAL COMPONENT DATA

MKDS 10 HV/ 2-ZB-10,16 1709681 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 10 HV/ 2-ZB-10,16



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 10 HV/ 2-ZB-10,16
Catalog number	1709681
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-B9A6B68EA9
Generated	2026-08-01

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 76 A, nominal voltage (III/2): 1000 V, nominal cross-section: 16 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: MKDS 10 HV, pitch: 10.16 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Zigzag Pins W, Pin length [P]: 5 mm, number of soldering pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1709681

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 453 (C-1-2013)

GTIN 4046356073769

Weight per Piece (excluding packing) 16.730 g

Custom tariff number 85369010

Country of origin CN (China)

Item properties

Brief article description PCB terminal block

Range of articles MKDS 10 HV

Pitch 10.16 mm

Number of positions 2

Connection method Screw connection with tension sleeve

Drive form screw head Slotted (L)

Screw thread M4

Mounting type Wave soldering

Pin layout Zigzag pinning W

Number of levels 1

Number of connections 2

Number of potentials 2

Electrical parameters

Rated current 76 A

Rated insulation voltage (III/2) 1000 V

Rated surge voltage (III/2) 8 kV

Connection capacity

Conductor cross section solid 0.5 mm² ... 16 mm²

Conductor cross section flexible 0.5 mm² ... 16 mm²

Conductor cross section AWG / kcmil 20 ... 6

Conductor cross section flexible, with ferrule without plastic sleeve 0.5 mm² ... 16 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.5 mm² ... 16 mm²

2 conductors with same cross section, solid 0.5 mm² ... 6 mm²

2 conductors with same cross section, flexible 0.5 mm² ... 6 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.5 mm² ... 4 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 6 mm²

Stripping length 10 mm

Torque 1.2 Nm ... 1.5 Nm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 10 HV/ 2-ZB-10,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.