

INDUSTRIAL COMPONENT DATA

MKDS 3/ 2-B-5,08 BU 1706439 PHOENIX CONTACT PCB terminal block, Nominal current: 24 A, Nom. voltage: 400 V, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 3/ 2-B-5,08 BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 3/ 2-B-5,08 BU
Catalog number	1706439
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-13C87C7FD0
Generated	2026-08-03

Product Overview

PCB terminal block, Nominal current: 24 A, Nom. voltage: 400 V, Pitch: 5.08 mm, Number of positions: 2, Connection method: Screw connection with tension sleeve, Mounting: Wave soldering, Conductor/PCB connection direction: 0 °, Color: blue, Connections internally jumpered

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 400 V, nominal section: 2.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, family of articles: MKDS 3/.. -B, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: blue, Pin arrangement: Linear pin arrangement, Pin length [P]: 5 mm, number of potential solder pins: 1, Packing type: Boxed packed. Internally bridged connections

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Dimensions

Length 11.2 mm

Pitch 5.08 mm

Dimension a 5.08 mm

Constructional height 18 mm

Length of the solder pin 5 mm

Pin dimensions 0,9 x 0,9 mm

Hole diameter 1.3 mm

General

Range of articles MKDS 3/..-B
Insulating material group I
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 250 V
Rated voltage (III/2) 400 V
Rated voltage (II/2) 630 V
Connection in acc. with standard EN-VDE
Nominal current IN 24 A
Nominal cross section 2.5 mm²
Maximum load current 28 A (with 4 mm² conductor cross section)
Insulating material PA
Solder pin surface Sn
Flammability rating according to UL 94 V0
Internal cylindrical gage A3
Stripping length 8 mm
Number of positions 2
Screw thread M3
Tightening torque, min 0.5 Nm
Tightening torque max 0.6 Nm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 3/ 2-B-5,08 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.