

INDUSTRIAL COMPONENT DATA

MKDSP 25/ 2-15,00 1932588 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSP 25/ 2-15,00



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSP 25/ 2-15,00
Catalog number	1932588
Category	Printed circuit board terminal
Minimum order	25 Pcs
Document ID	EO-DADF37357C
Generated	2026-08-02

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 125 A, nominal voltage (III/2): 1000 V, nominal cross-section: 35 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: MKDSP 25, pitch: 15 mm, connection type: Screw connection with traction capsule, screw clamping method: Z2L Pozidriv with longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 4.5 mm, number of soldering pins per potential: 4, packaging type: boxed packaging. Permanent mechanical loads on the terminal block must be avoided

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1932588

Packing unit 25 pc

Minimum order quantity 25 pc

Catalog page Page 455 (C-1-2013)

GTIN 4017918902087

Weight per Piece (excluding packing) 43.640 g

Custom tariff number 85369010

Country of origin SK (Slovakia)

Item properties

Brief article description PCB terminal block

Range of articles MKDSP 25

Pitch 15 mm

Number of positions 2

Connection method Screw connection with tension sleeve

Drive form screw head Philipps recess with slotted Torx (H1L)

Screw thread M5

Mounting type Wave soldering

Pin layout Linear pinning

Number of levels 1

Number of connections 2

Number of potentials 2

Electrical parameters

Rated current 125 A

Rated insulation voltage (III/2) 1000 V

Rated surge voltage (III/2) 8 kV

Connection capacity

Conductor cross section solid 0.5 mm² ... 35 mm²Conductor cross section flexible 0.5 mm² ... 35 mm²

Conductor cross section AWG / kcmil 20 ... 2

Conductor cross section flexible, with ferrule without plastic sleeve 1 mm² ... 35 mm²Conductor cross section, flexible, with ferrule, with plastic sleeve 1.5 mm² ... 35 mm²2 conductors with same cross section, solid 0.5 mm² ... 6 mm²2 conductors with same cross section, flexible 0.5 mm² ... 6 mm²2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.5 mm² ... 4 mm²2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 16 mm²

Stripping length 18 mm

Torque 2.5 Nm ... 4.5 Nm ($\leq 25 \text{ mm}^2 = 2.5 \text{ Nm}$; $35 \text{ mm}^2 = 4.5 \text{ Nm}$)

Materi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSP 25/ 2-15,00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.