


INDUSTRIAL COMPONENT DATA

PT 1,5/ 3-3,5-V 1984772 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 3-3,5-V



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/ 3-3,5-V
Catalog number	1984772
Category	Printed circuit board terminal
Minimum order	250 Pcs
Document ID	EO-124F1889F3
Generated	2026-08-03

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 17.5 A, nominal voltage (III/2): 200 V, nominal section: 1.5 mm², number of potentials: 3, number of rows: 1, number of poles per row: 3, family of articles: PT 1.5/.. -V, pitch: 3.5 mm, connection type: Screw connection with wire protection bracket, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 4.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1984772

Packing unit 250 pc

Minimum order quantity 250 pc

Catalog page Page 419 (C-1-2013)

GTIN 4017918946326

Weight per Piece (excluding packing) 1.370 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [l] 9.15 mm

Pitch 3.5 mm

Dimension a 7 mm

Width [w] 10.5 mm

Height 7.55 mm

Height [h] 12.05 mm

Solder pin [P] 4.5 mm

Pin spacing 3.5 mm

Hole diameter 1.2 mm

General

Range of articles PT 1,5/..-V

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 200 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current I_N 17.5 A

Nominal cross section 1.5 mm²

Maximum load current 17.5 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 5 mm

Number of positions 3

Screw thread M2

Tightening torque, min 0.22 Nm

Tightening torque max 0.25 Nm

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.2 mm²

2 con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 3-3,5-V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.