

## INDUSTRIAL COMPONENT DATA

# PTSA 1,5/12-3,5-Z 1985292 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSA 1,5/12-3,5-Z



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | PTSA 1,5/12-3,5-Z              |
| Catalog number  | 1985292                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 80 Pcs                         |
| Document ID     | EO-945E79EF27                  |
| Generated       | 2026-08-04                     |

## Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 8 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm<sup>2</sup>, number of potentials: 12, number of rows: 1, number of poles per row: 12, article family: PTSA 1.5, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: green, Pin arrangement: Zigzag Pins W, Pin length [P]: 3.5 mm, number of welding pins per potential: 1, packaging type: boxed packaging. Offset welding pins, two rows

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1985292

Packing unit 80 pc

Minimum order quantity 80 pc

Note Made to Order (non-returnable)

Catalog page Page 413 (C-1-2013)

GTIN 4017918922375

Weight per Piece (excluding packing) 5.840 g

Custom tariff number 85369010

Country of origin DE (Germany)

**Dimensions**

Length [ l ] 12 mm

Pitch 3.5 mm

Dimension a 38.5 mm

Width [ w ] 43.5 mm

Height 13.1 mm

Height [ h ] 16.7 mm

Solder pin [P] 3.6 mm

Pin spacing 3.5 mm

Hole diameter 1 mm

**General**

Range of articles PTSA 1,5

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm<sup>2</sup>

Maximum load current 8 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 9 mm

Number of positions 12

**Connection data**Conductor cross section solid min. 0.2 mm<sup>2</sup>Conductor cross section solid max. 1.5 mm<sup>2</sup>Conductor cross section flexible min. 0.2 mm<sup>2</sup>Conductor cross section flexible max. 1.5 mm<sup>2</sup>Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>Conductor cross section flexible, with ferrule without plastic sleeve max. 1 mm<sup>2</sup>Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm<sup>2</sup>

Conductor cross section AWG mi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSA 1,5/12-3,5-Z with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.