


INDUSTRIAL COMPONENT DATA

SMKDS 1/10-3,5 1751170 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDS 1/10-3,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMKDS 1/10-3,5
Catalog number	1751170
Category	Printed circuit board terminal
Minimum order	100 Pcs
Document ID	EO-A283D21D93
Generated	2026-08-01

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 10 A, nominal voltage (III/2): 200 V, nominal cross-section: 1 mm², number of potentials: 10, number of rows: 1, number of poles per row: 10, article family: SMKDS 1, pitch: 3.5 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 35 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

PCB terminal, Rated current: 10 A, Rated voltage (III/2): 200 V, Nominal cross-section: 1 mm², Number of potentials: 10, Number of rows: 1, Number of poles per row: 10, Product family: SMKDS 1, Pitch: 3.5 mm, Connection type: Screw connection with pull sleeve, Screw attack shape: L Longitudinal slot, Mounting: Wave soldering, Connection direction conductor/board: 35 °, Color: Green, Pin layout: Linear pinning, Pin length [P]: 3.5 mm, Number of solder pins per potential: 1, Packing type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1751170

Packing unit 100 pc

Catalog page Page 85 (C-1-2013)

GTIN 4017918103774

Weight per Piece (excluding packing) 5.790 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [l] 10 mm

Pitch 3.5 mm

Dimension a 31.5 mm

Width [w] 35.5 mm

Height 9.5 mm

Height [h] 13 mm

Solder pin [P] 3.5 mm

Hole diameter 1.1 mm

General

Range of articles SMKDS 1

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 200 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current I_N 10 A

Nominal cross section 1 mm²

Maximum load current 12 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 5 mm

Number of positions 10

Screw thread M2

Tightening torque, min 0.22 Nm

Tightening torque max 0.25 Nm

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 0.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²

Conductor cross section AWG min...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDS 1/10-3,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.