

INDUSTRIAL COMPONENT DATA

SPT 16/ 2-H-10,0-ZB 1735781 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 16/ 2-H-10,0-ZB



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 16/ 2-H-10,0-ZB
Catalog number	1735781
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-7BA4584833
Generated	2026-08-01

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 76 A, nominal voltage (III/2): 1000 V, nominal section: 16 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, family of articles: SPT 16/.. -H, pitch: 10 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: W zigzag pins, Pin length [P]: 4 mm, number of solder pins per potential: 3, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1735781

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 467 (C-1-2013)

GTIN 4046356179423

Weight per Piece (excluding packing) 16.350 g

Custom tariff number 85369010

Country of origin BG (Bulgaria)

Item properties

Brief article description PCB terminal block

Range of articles SPT 16/...-H

Pitch 10 mm

Number of positions 2

Connection method Push-in spring connection

Mounting type Wave soldering

Pin layout Zigzag pinning W

Number of levels 1

Number of connections 2

Number of potentials 2

Electrical parameters

Rated current 76 A

Rated insulation voltage (III/2) 1000 V

Rated surge voltage (III/2) 8 kV

Connection capacityConductor cross section solid 0.75 mm² ... 16 mm²Conductor cross section flexible 0.75 mm² ... 16 mm²

Conductor cross section AWG / kcmil 20 ... 4

Conductor cross section flexible, with ferrule without plastic sleeve 0.75 mm² ... 16 mm²Conductor cross section, flexible, with ferrule, with plastic sleeve 0.75 mm² ... 10 mm²2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.75 mm² ... 4 mm²

Stripping length 18 mm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics Tin-plated

Metal surface terminal point (top layer) Tin (10 - 16 µm Sn)

Metal surface soldering area (top layer) Tin (10 - 16 µm Sn)

Material data - housing

Insulating material...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 16/ 2-H-10,0-ZB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.