


INDUSTRIAL COMPONENT DATA

SPT 2,5/ 4-V-5,0 1991118 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 2,5/ 4-V-5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 2,5/ 4-V-5,0
Catalog number	1991118
Category	Printed circuit board terminal
Minimum order	120 Pcs
Document ID	EO-C8CF3B14B8
Generated	2026-08-03

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 400 V, nominal section: 2.5 mm², number of potentials: 4, number of rows: 1, number of poles per row: 4, family of articles: SPT 2.5/.. -V, pitch: 5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 90 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.5 mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1991118

Packing unit 100 pc

Minimum order quantity 100 pc

Catalog page Page 143 (C-1-2013)

GTIN 4046356104739

Weight per Piece (excluding packing) 5.360 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [l] 13.5 mm

Pitch 5 mm

Dimension a 15 mm

Width [w] 21.4 mm

Height 14.4 mm

Height [h] 16.9 mm

Solder pin [P] 2.5 mm

Pin spacing 5 mm

Hole diameter 1.1 mm

General

Range of articles SPT 2,5/..-V

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 24 A

Nominal cross section 2.5 mm²

Maximum load current 24 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 10 mm

Number of positions 4

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm² Stripping length 8 mm

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm² Stripping length 8 mm

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm² Stripping length 8 mm

Conductor cross section flexible, with ferrule...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 2,5/ 4-V-5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.