


INDUSTRIAL COMPONENT DATA

SPT 5/ 4-V-7,5-ZB 1719338 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 5/ 4-V-7,5-ZB



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 5/ 4-V-7,5-ZB
Catalog number	1719338
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-91D8EE81FC
Generated	2026-08-03

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 41 A, nominal voltage (III/2): 1000 V, nominal section: 6 mm², number of potentials: 4, number of rows: 1, number of poles per row: 4, family of articles: SPT 5/.. -V, pitch: 7.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: green, Pin arrangement: Zigzag pins W, Pin length [P]: 4.6 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1719338

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 465 (C-1-2013)

GTIN 4046356141437

Weight per Piece (excluding packing) 13.920 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [l] 18.5 mm

Pitch 7.5 mm

Dimension a 22.5 mm

Width [w] 31.8 mm

Height 14.4 mm

Height [h] 19 mm

Solder pin [P] 4.6 mm

Pin spacing 14 mm

Hole diameter 2.1 mm

General

Range of articles SPT 5/..-V

Insulating material group I

Rated surge voltage (III/3) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 800 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 41 A

Nominal cross section 6 mm²

Maximum load current 41 A

Insulating material PA

Contact material Sn

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 15 mm

Number of positions 4

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 10 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 6 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²

Conductor cross section AWG min. 24

Conductor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 5/ 4-V-7,5-ZB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.