

## INDUSTRIAL COMPONENT DATA

# SPT 5/ 5-H-7,5-ZB 1719228 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 5/ 5-H-7,5-ZB



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | SPT 5/ 5-H-7,5-ZB              |
| Catalog number  | 1719228                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 50 Pcs                         |
| Document ID     | EO-1117315809                  |
| Generated       | 2026-08-03                     |

## Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 41 A, nominal voltage (III/2): 1000 V, nominal section: 6 mm<sup>2</sup>, number of potentials: 5, number of rows: 1, number of poles per row: 5, family of articles: SPT 5/.. -H, pitch: 7.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: green, Pin arrangement: Zigzag pins W, Pin length [P]: 4.6 mm, number of solder pins per potential: 2, packaging type: boxed

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1719228

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 463 (C-1-2013)

GTIN 4046356141321

Weight per Piece (excluding packing) 18.040 g

Custom tariff number 85369010

Country of origin BG (Bulgaria)

**Dimensions**

Length [ l ] 24.15 mm

Pitch 7.5 mm

Dimension a 30 mm

Width [ w ] 39.3 mm

Height 19.6 mm

Height [ h ] 24.2 mm

Solder pin [P] 4.6 mm

Pin spacing 13.2 mm

Hole diameter 2.1 mm

**General**

Range of articles SPT 5/..-H

Insulating material group I

Rated surge voltage (III/3) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (II/2) 8 kV

Rated voltage (III/3) 800 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 41 A

Nominal cross section 6 mm<sup>2</sup>

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 15 mm

Number of positions 5

**Connection data**Conductor cross section solid min. 0.2 mm<sup>2</sup>Conductor cross section solid max. 10 mm<sup>2</sup>Conductor cross section flexible min. 0.2 mm<sup>2</sup>Conductor cross section flexible max. 6 mm<sup>2</sup>Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm<sup>2</sup>Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm<sup>2</sup>

Conductor cross section AWG min. 24

Conductor cross...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 5/ 5-H-7,5-ZB with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.