

INDUSTRIAL COMPONENT DATA

ZFKDSA 10-11,7 1987054 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFKDSA 10-11,7



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFKDSA 10-11,7
Catalog number	1987054
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-89458F0BE5
Generated	2026-08-01

Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 76 A, rated voltage (III/2): 400 V, nominal cross-section: 10 mm², number of potentials: 1, number of rows: 1, number of poles per row: 1, article family: ZFKDS(A) 10, pitch: 10 mm, connection type: Spring connection, mounting: Wave soldering, driver/printed circuit board connection direction: 45 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 6.5 mm, number of welding pins per potential: 4, packaging type: boxed. The item can be aligned with different numbers of poles!

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1987054

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 479 (C-1-2013)

GTIN 4017918973162

Weight per Piece (excluding packing) 11.470 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [l] 33.4 mm

Pitch 10 mm

Width [w] 11.7 mm

Height 27 mm

Height [h] 33.5 mm

Solder pin [P] 6.5 mm

Pin spacing 15 mm

Hole diameter 2.2 mm

General

Range of articles ZFKDS(A) 10

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 320 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 800 V

Connection in acc. with standard EN-VDE

Nominal current I_N 76 A

Nominal cross section 10 mm²

Maximum load current 76 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 12 mm

Number of positions 1

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 16 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 16 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 10 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 6

Standards and...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFKDSA 10-11,7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.