


INDUSTRIAL COMPONENT DATA

ZFKKDS 1,5C-5,0 1889301 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFKKDS 1,5C-5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFKKDS 1,5C-5,0
Catalog number	1889301
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-3A360CB18E
Generated	2026-08-01

Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 16 A, rated voltage (III/2): 400 V, rated cross-section: 1.5 mm², number of potentials: 2, number of rows: 2, number of poles per row: 1, article family: ZFKKDS(A) 1.5C, pitch: 5 mm, connection type: Spring connection, mounting: Wave soldering, driver/printed circuit board connection direction: 45 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.7 mm, number of solder pins per potential: 1, packaging type: boxed. Individual disc for the individual composition of different numbers of poles. To complete the block, an additional terminal block is required (see accessories). Block-bound items in different numbers of poles are also available.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1889301

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 131 (C-1-2013)

GTIN 4017918167967

Weight per Piece (excluding packing) 2.800 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [l] 21 mm

Pitch 5 mm

Width [w] 5 mm

Height 26 mm

Height [h] 29.7 mm

Solder pin [P] 3.7 mm

Hole diameter 1.1 mm

General

Range of articles ZFKKDS(A) 1,5C

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 16 A

Nominal cross section 1.5 mm²Maximum load current 16 A (with a 2.5 mm² conductor cross section)

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 7 mm

Number of positions 1

Connection dataConductor cross section solid min. 0.2 mm²Conductor cross section solid max. 2.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 1.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²

Conductor cross section AWG min....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFKKDS 1,5C-5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.