

INDUSTRIAL COMPONENT DATA

MKDSO 2,5 HV/ 2R-7,5 KMGY 2199773 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSO 2,5 HV/ 2R-7,5 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSO 2,5 HV/ 2R-7,5 KMGY
Catalog number	2199773
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-B1877A681B
Generated	2026-08-01

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 630 V, nominal section: 2.5 mm², number of rows: 1, number of poles per row: 2, article family: MKDSO 2.5 HV/.. -R, pitch: 7.5 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: light gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.25 mm, number of solder pins per potential: 1. Item with side pin output on the right

PCB terminal block, rated current: 24 A, sizing voltage (III/2): 630 V, nominal cross-section: 2.5 mm², number of rows: 1, number of poles per row: 2, product series: MKDSO 2.5 HV/.. -R, pitch: 7.5 mm, connection type: Screw connection with cage, mounting: Wave soldering, conductor/board connection direction: 0°, color: light gray, Pin layout: Linear pinning, Pin length [P]: 2.25 mm, number of solder pins per potential: 1. Item with right side pin output

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2199773

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 125 (C-1-2013)

GTIN 4046356464253

Weight per Piece (excluding packing) 4.890 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Pitch 7.5 mm

Dimension a 7.5 mm

Solder pin [P] 3.5 mm

Hole diameter 1.4 mm

General

Range of articles MKDSO 2,5 HV/..-R

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 600 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 24 A

Nominal cross section 2.5 mm²

Maximum load current 24 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A2

Stripping length 8 mm

Number of positions 2

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conduc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSO 2,5 HV/ 2R-7,5 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.