

INDUSTRIAL COMPONENT DATA

PTSM 0,5/ 3-2,5-V SMD R44 1771101 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSM 0,5/ 3-2,5-V SMD R44



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTSM 0,5/ 3-2,5-V SMD R44
Catalog number	1771101
Category	Printed circuit board terminal
Minimum order	400 Pcs
Document ID	EO-CF7679DFC8
Generated	2026-08-01

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 6 A, nominal voltage (III/2): 160 V, nominal section: 0.5 mm², number of potentials: 3, number of rows: 1, number of poles per row: 3, family of articles: PTSM 0,5/..-V-SMD, pitch: 2.5 mm, connection type: Push-in spring connection, mounting: SMD soldering, driver/printed circuit board connection direction: 90°, color: black, Pin arrangement: Linear pin arrangement, number of potential solder pins: 1, packaging type: 44 mm wide strap

Printed circuit board terminal, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.5 mm², number of potentials: 3, number of rows: 1, number of positions per row: 3, product range: PTSM 0,5/..-V-SMD, pitch: 2.5 mm, connection method: Push-in spring connection, mounting: SMD soldering, conductor/PCB connection direction: 90°, color: black, Pin layout: Linear pad geometry, number of solder pins per potential: 1, type of packaging: 44 mm wide tape

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family PTSM 0,5/..-V-SMD

Product line COMBICON Terminals XS

Number of positions 3

Pitch 2.5 mm

Number of connections 3

Number of rows 1
Number of potentials 3
Pin layout Linear pad geometry
Solder pins per potential 1
Data management status
Article revision 00
Electrical propertiesNominal current IN 6 A
Nominal voltage UN 160 V
Rated voltage (III/3) 32 V
Rated surge voltage (III/3) 2.5 kV
Rated voltage (III/2) 160 V
Rated surge voltage (III/2) 2.5 kV
Rated voltage (II/2) 160 V
Rated surge voltage (II/2) 2.5 kV
Connection dataConnection technology
Nominal cross section 0.5 mm²
Conductor connection
Connection method Push-in spring connection
Conductor cross section rigid 0.14 mm² ... 0.5 mm²
Conductor cross section flexible 0.2 mm² ... 0.5 mm² (up to 0.75 mm² supported, with a stripping length of 7.5 mm and a rated insulation voltage of 32 V at III/2)
Conductor cross section AWG 26 ... 20
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 0.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.34 mm² (possible from 0.14 mm², when using ferrule AI 0.14- 6 GY in combination with crimping pliers CRIMPFOX 10T-F)
Cylindrical gauge a x b / diameter - / 1.2 mm
Stripping length 6 mm
MountingMounting type SMD soldering
Pin layout Linear pad geometry
Processing notes
Process Reflow soldering
Moisture Sensitive Level MSL 1
Classification....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSM 0,5/ 3-2,5-V SMD R44 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.