

INDUSTRIAL COMPONENT DATA

PTSM 0,5/ 6-2,5-H SMD R44 1771062 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSM 0,5/ 6-2,5-H SMD R44



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTSM 0,5/ 6-2,5-H SMD R44
Catalog number	1771062
Category	Printed circuit board terminal
Minimum order	770 Pcs
Document ID	EO-17BF59DDDD
Generated	2026-08-04

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 6 A, nominal voltage (III/2): 160 V, nominal section: 0.5 mm², number of potentials: 6, number of rows: 1, number of poles per row: 6, family of articles: PTSM 0.5/.. -H-SMD, pitch: 2.5mm, connection type: Push-in spring connection, mounting: SMD soldering, conductor/printed circuit board connection direction: 0°, color: black, Pin arrangement: Linear pin arrangement, number of solder pins per potential: 1, packing type: 44mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1771062

Packing unit 770 pc

Minimum order quantity 770 pc

Catalog page Page 53 (C-1-2013)

GTIN 4046356459716

Weight per Piece (excluding packing) 2.000 g

Custom tariff number 85369010

Country of origin IN (India)

Dimensions

Length [l] 9 mm

Pitch 2.5 mm

Dimension a 12.5 mm

Width [w] 17.6 mm

Height 5.12 mm

Height [h] 5.12 mm

General

Range of articles PTSM 0,5/..-H-SMD

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 32 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 160 V

Connection in acc. with standard EN-VDE

Nominal current I_N 6 A

Nominal cross section 0.5 mm²

Maximum load current 6 A

Insulating material LCP

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 6 mm

Number of positions 6

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 0.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 0.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 0.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 20

Standards and Regulations

Connection in acc. with standard EN-VDE

UL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlim...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSM 0,5/ 6-2,5-H SMD R44 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.