

**INDUSTRIAL COMPONENT DATA**

# PCH 6/ 4+4-G-7,62 P26THR 1192659 PHOENIX CONTACT

## Hybrid base strip for circ plate. printed, nominal section:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PCH 6/ 4+4-G-7,62 P26THR



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | PCH 6/ 4+4-G-7,62 P26THR        |
| Catalog number  | 1192659                         |
| Category        | Printed circuit board connector |
| Minimum order   | 50 Pcs                          |
| Document ID     | EO-DEEF3231F3                   |
| Generated       | 2026-08-05                      |

### Product Overview

Hybrid base strip for circ plate. printed, nominal section: 6 mm<sup>2</sup>, color: black, nominal current: 41 A, 8 A, nominal voltage (III/2): 630 V, contact surface: Sn, contact connection type: Male, number of rows: 1, number of poles: 8, article family: PCH 6/.. +4-G-THR, pitch: 7.62 mm, mounting: THR welding/wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 6 hybrid, Plug-in face orientation: Standard, locking: Snap-in lock, clamping type: without, packaging type: boxed

Hybrid base strip for circ plate. printed, nominal section: 6 mm<sup>2</sup>, colour: black, rated current: 41 A, 8 A, dimensioning voltage (III/2): 630 V, surface contacts: Tin, contact type: Male, number of rows: 1, number of poles: 8, article family: PCH 6/.. +4-G-THR, pitch: 7.62 mm, mounting: Welding THR, pin length [P]: 2.6 mm, number of welding pins per potential: 3, plug-in system: POWER COMBICON 6 Hybrid, Plug-in face orientation: Standard, Locking: Locking by socket, fixing type: without, type of packaging: boxed packaging

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

### Additional Product Information

ETIM for 1192659 Connectors (EC002637)

Feature Name

Feature Value

Contact type (EF001587)

Pin

Number of poles (EF001391)

4

Modular spacing contacts (EF007326)

7.62 mm

Modular spacing connections (EF006827)

7.62 mm

Rated current  $I_n$  (EF008250)

41 A

Rated voltage (EF000228)

630 V

Material of contact surface (EF004020)

Tin

Diameter connection pin (EF006823)

1.75 mm

Length pin (EF006825)

2.6 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Black

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of banding (EF007011)

Carton (for SMD)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PCH 6/ 4+4-G-7,62 P26THR with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.