

**INDUSTRIAL COMPONENT DATA**

# PCV 5/ 3-GF-15,24 1392187 PHOENIX CONTACT Printed circuit board base housing, nominal section: 6 mm<sup>2</sup>, color:...

Brand: PHOENIX CONTACT | Manufacturer Part Number: PCV 5/ 3-GF-15,24



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | PCV 5/ 3-GF-15,24               |
| Catalog number  | 1392187                         |
| Category        | Printed circuit board connector |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-F7455DF731                   |
| Generated       | 2026-08-05                      |

## Product Overview

PCV 5/ 3-GF-15,24 1392187 PHOENIX CONTACT Printed circuit board base housing, nominal section: 6 mm<sup>2</sup>, color:...**STRUCTURED PRODUCT DATA**

## Technical Specifications

| TECHNICAL ATTRIBUTE                       | VALUE           |
|-------------------------------------------|-----------------|
| Connector model (EF007495)                | Fixed connector |
| Contact type (EF001587)                   | Pin             |
| Number of plug-in contact rows (EF006935) | 1               |
| Modular spacing contacts (EF007326)       | 15.24 mm        |
| Modular spacing connections (EF006827)    | 15.24 mm        |
| Rated current I <sub>n</sub> (EF008250)   | 41 A            |
| Rated voltage (EF000228)                  | 1000 V          |
| Rated surge voltage (EF002993)            | 8 kV            |
| Over voltage category (EF006785)          | III             |
| Pollution degree (EF006786)               | 2               |
| Material of contact surface (EF004020)    | Tin             |
| Type of electric connection (EF003961)    | Other           |
| Diameter connection pin (EF006823)        | 1.3 mm          |
| Length pin (EF006825)                     | 5 mm            |
| Material insulation body (EF007543)       | Other           |

**CONTINUED**

## Technical Specifications

| TECHNICAL ATTRIBUTE                                                      | VALUE            |
|--------------------------------------------------------------------------|------------------|
| Housing colour (EF000136)                                                | Green            |
| Inflammability class of insulation material according to UL94 (EF002521) | V0               |
| Operating temperature (EF002393)                                         | -40 °C           |
| Type of fastening (EF002442)                                             | Other            |
| Type of banding (EF007011)                                               | Carton (for SMD) |

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| eCl@ss 7.1   | 21043711                               |
| eCl@ss 8.0   | 21043711                               |
| eCl@ss 9.0   | 21043711                               |
| ETIM 5.0     | EC002246                               |
| ETIM 6.0     | EC002246                               |
| ETIM 7.0     | EC002246                               |
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Printed circuit board base housing, nominal section: 6 mm<sup>2</sup>, color: green, nominal current: 41 A, nominal voltage (III/2): 1000 V, contact surface: Sn, contact connection type: Male, number of rows: 1, number of poles: 3, family of articles: PCV 5/.. -GF, pitch: 15.24 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 5 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

Base housing printed circuit board, nominal section: 6 mm<sup>2</sup>, color: green, rated current: 41 A, dimensioning voltage (III/2): 1000 V, surface contacts: Tin, contact type: Male, number of rows: 1, number of poles: 3, article family: PCV 5/.. -GF, pitch: 15.24 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 5 mm, number of welding pins per potential: 3, plug-in system: POWER COMBICON 5, Plug-in face orientation: Standard, Locking: Screw lock, fixing type: Aerial fastening (thread), packaging type: box packaging

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PCV 5/ 3-GF-15,24 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.