


INDUSTRIAL COMPONENT DATA

PCV 6-16/ 9-G-10,16 1922556 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: PCV 6-16/ 9-G-10,16



Manufacturer	PHOENIX CONTACT
MPN / Reference	PCV 6-16/ 9-G-10,16
Catalog number	1922556
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-08B36A0D81
Generated	2026-08-05

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 6 mm², color: green, nominal current: 76 A (41 A in combination with PC 6 connector), nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Male, number of potentials: 9, number of rows: 1, number of poles: 9, number of connections: 9, family of articles: PCV 6-16/.. -G, pitch: 10.16 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, number of soldering pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: box-packed, The 76 A rated current is valid in combination with PC 16 family connectors. In combination with PC 6 connectors, 41 A (50 A according to UL) is achieved.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1922556

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 195 (CC-2002)

GTIN 4017918727086

Weight per Piece (excluding packing) 31.090 g

Custom tariff number 85366930

Country of origin PL (Poland)

Dimensions

Pitch 10.16 mm

Dimension a 81.28 mm

Height 29 mm

Length of the solder pin 4 mm

Pin dimensions 0.8 x 1.2 mm

General

Range of articles PCV 6-16/..-G

Rated voltage (III/3) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 76 A

Color green

Number of positions 9

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC

13.239121409

ETIM for 1922556 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

9

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

10.16 mm

Modular spacing connections (EF006827)

10.16 mm

Rated current In (EF008250)

76 A

Rated voltage (EF000228)

1000 V

Rated surge voltage (EF002993...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PCV 6-16/ 9-G-10,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.