

INDUSTRIAL COMPONENT DATA

QUINT-UPS/ 24DC/ 24DC/10/3.4AH 2320267 PHOENIX CONTACT Uninterruptible power supply

Brand: PHOENIX CONTACT | Manufacturer Part Number: QUINT-UPS/ 24DC/ 24DC/10/3.4AH



Manufacturer	PHOENIX CONTACT
MPN / Reference	QUINT-UPS/ 24DC/ 24DC/10/3.4AH
Catalog number	2320267
Category	UPS
Minimum order	1 Pcs
Document ID	EO-13AF73313D
Generated	2026-08-01

Product Overview

Uninterruptible power supply

Uninterruptible power supply with IQ technology and integrated energy storage for rail mounting, input: 24VDC, output: 24VDC / 10A, energy storage: 4Ah lead AGM, incl. universal adapter for UTA 107/30 rail mounted

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Power Supplies (PS)
--------------	---------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2320267

Packing unit 1 pc

Catalog page Page 294 (C-4-2017)

GTIN 4046356554183

Weight per Piece (excluding packing) 4,434.000 g

Custom tariff number 85371091

Country of origin CN (China)

Dimensions

Width 120 mm

Height 169 mm

Depth 125 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) 0 °C ... 40 °C

Ambient temperature (storage/transport) -15 °C ... 40 °C

Max. permissible relative humidity (operation) ≤ 95 % (25 °C, non-condensing)

Climatic class 3K3 (in acc. with EN 60721)

Degree of pollution 2

Input data

Input voltage 24 V DC

Input voltage range 18 V DC ... 30 V DC

Current consumption (maximum) 18.6 A (24 V DC)

Current consumption (idle) 9.5 mA

Current consumption (charging process) 3.6 A

Output data (24 V DC mains operation)

Nominal output voltage 24 V DC

Output voltage range (depends on the input voltage) 18 V DC ... 30 V DC

Nominal output current (IN) 10 A (0 °C ... 40 °C)

POWER BOOST (IBoost) 15 A (0 °C ... 40 °C)

Selective Fuse Breaking (ISFB) 60 A (0 °C ... 40 °C)

Output data (24 V DC battery operation)

Nominal output voltage 24 V DC

Output voltage range (depends on the input voltage) 19.2 V DC ... 27.6 V DC (UOUT= UBAT- 0.5 V DC)

Nominal output current (IN) 10 A (0 °C ... 40 °C)

POWER BOOST (IBoost) 15 A (0 °C ... 40 °C)

Selective Fuse Breaking (ISFB) 65 A (0 °C ... 40 °C)

General output data

Efficiency > 97.6 % (Mains operation, with charged energy storage)

General

IQ technology Yes

Disposal Used batteries mu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QUINT-UPS/ 24DC/ 24DC/10/3.4AH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.