

INDUSTRIAL COMPONENT DATA

AGK 10-PTPOWER BU 3260148 PHOENIX CONTACT Pick-off terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: AGK 10-PTPOWER BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	AGK 10-PTPOWER BU
Catalog number	3260148
Category	Terminal block connector
Minimum order	10 Pcs
Document ID	EO-FC2687DDCA
Generated	2026-08-02

Product Overview

Pick-off terminal block

Branch terminal, nominal voltage: 1500 V, nominal current: 57 A, number of connections: 2, connection type: Push-in connection, 1st floor, Dimensioning section: 10 mm², cross-section: 0.5 mm² - 16 mm², mounting class: on base element, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3260148

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 126 (C-1-2017)

GTIN 4046356779081

Weight per Piece (excluding packing) 22.600 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note For use with PTPOWER 50, 95, and 150 Power-Turn high-current terminal blocks

Number of levels 1

Number of connections 2
Potentials 1
Nominal cross section 10 mm²
Color blue
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.82 W
Maximum load current 57 A (with 16 mm² conductor cross section)
Nominal current I_N 57 A
Nominal voltage U_N 1500 V
Open side panel No
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AGK 10-PTPOWER BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.