

INDUSTRIAL COMPONENT DATA

PLA 5/ 3-7,5-ZF GY 1015762 PHOENIX CONTACT Terminal for printed circuit board, rated voltage: 1000 V, pitch:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLA 5/ 3-7,5-ZF GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLA 5/ 3-7,5-ZF GY
Catalog number	1015762
Category	Printed circuit board terminal
Minimum order	25 Pcs
Document ID	EO-9CEBD136AF
Generated	2026-08-06

Product Overview

Terminal for printed circuit board, rated voltage: 1000 V, pitch: 7.5 mm, number of poles: 3, type of connection: Connection by spring loaded push lock, mounting: Soldering by wave, color: gray

Terminal block for printed circuit board, nominal current: 41 A, dimensioning voltage (III/2): 1000 V, nominal section: 6 mm², number of potentials: 3, number of rows: 1, number of poles per row: 3, article family: PLA 5/, pitch: 7.5 mm, connection type: Spring push lock connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 30 °, color: gray, Pin arrangement: Double linear pin arrangement, Pin length [P]: 3.6 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLA 5/ 3-7,5-ZF GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.