

INDUSTRIAL COMPONENT DATA

EMLP 32 (38X14) SR CUS 0824373 PHOENIX CONTACT Plastic label with drill hole

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMLP 32 (38X14) SR CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMLP 32 (38X14) SR CUS
Catalog number	0824373
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-C67E08A859
Generated	2026-08-02

Product Overview

Plastic label with drill hole

Plastic sign with hole, available: per card, silver, labelled according to customer specifications, mounting class: glued, usable area: 38 x 14 mm, Number of individual indexes: 6

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > CABINET add-on**

Additional Product Information

Key Commercial Data

Orderkey 0824373

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 295 (C-5-2013)

GTIN 4046356352499

Weight per Piece (excluding packing) 21.690 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 50 mm

Width (a) 38 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 80 °C

Recommended storage conditions 20°C/50% relative humidity. Storage in the original packaging is recommended.

General

Color silver

Components free from silicone and halogen

Material TRANSPLY-ABS

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 6

Number of individual labels per row 2

Adhesive Acrylic

Printability Plotter

Engraving

Device 5144615 CMS-P1-PLOTTER

5145546 P1 ENGRAVING UNIT

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Adhesive strength 50 µm

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 10.0.127400629eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027149103eCl@ss 5.127...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMLP 32 (38X14) SR CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.