

INDUSTRIAL COMPONENT DATA

PLC-RPT- 24DC/ 1/ACT 2900312 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RPT-24DC/ 1/ACT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RPT-24DC/ 1/ACT
Catalog number	2900312
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-A5C24BE345
Generated	2026-07-31

Product Overview

Relay Module

PLC-INTERFACE for output functions, consisting of PLC-BPT.../ACT base terminal block with push-in connection and plug-in miniature relay with power contact, for mounting on NS 35/7.5 rail, 1 closing contact, input voltage 24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Relays**

Additional Product Information

Key Commercial Data

Orderkey 2900312

Packing unit 10 pc

Catalog page Page 378 (C-5-2017)

GTIN 4046356510004

Weight per Piece (excluding packing) 31.270 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 80 mm

Depth 94 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Coil side

Nominal input voltage UN 24 V DC

Typical input current at UN 9 mA

Typical response time 5 ms

Typical release time 8 ms

Protective circuit Reverse polarity protection Polarity protection diode

Free-wheeling diode Damping diode

Operating voltage display Yellow LED

Power dissipation for nominal condition 0.22 W

Contact side

Contact type 1 N/O contact

Type of switch contact Single contact

Contact material AgSnO

Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)

Minimum switching voltage 5 V (at 100 mA)

Min. switching current 10 mA (at 12 V)

Maximum inrush current 10 A (4 s)

Limiting continuous current 6 A

Interrupting rating (ohmic load) max. 140 W (at 24 V DC)

20 W (at 48 V DC)

18 W (at 60 V DC)

23 W (at 110 V DC)

40 W (at 220 V DC)

1500 VA (for 250 V AC)

Switching capacity 2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RPT-24DC/ 1/ACT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.