

INDUSTRIAL COMPONENT DATA

PLC-RSC- 24DC/ 1- 1/ACT 2967109 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RSC-24DC/ 1-1/ACT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RSC-24DC/ 1-1/ACT
Catalog number	2967109
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-1EE537EF98
Generated	2026-08-04

Product Overview

Relay Module

PLC-INTERFACE for output functions, consisting of PLC-BSC.../ACT base terminal block with screw connection and plug-in miniature relay with power contact, for mounting on NS 35/7.5 rail, 2 closing contacts (1-1), input voltage 24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Technical dataProduct propertiesProduct type Relay Module

Product family PLC-INTERFACE

Application Output function

Operating mode 100% operating factor

Mechanical service life 3x 10⁷cycles

Data management status

Date of last data management 11.07.2024

Article revision 11

Insulation characteristics: Air clearances and creepage distances between the power circuits

Insulation Basic insulation

Overvoltage category III

Pollution degree 2

Electrical propertiesMaximum power dissipation for nominal condition 0.43 W

Test voltage (Winding/contact) 4 kVrms(50 Hz, 1 min.)

Test voltage () 1 kVrms(50 Hz, 1 min.)

Test voltage (N/O contact / N/O contact) 2.5 kVrms(50 Hz, 1 min.)

Air clearances and creepage distances between the power circuits

Rated insulation voltage 250 V AC

Rated surge voltage 4 kV (Safe isolation, reinforced insulation, and 6 kV between input circuit and output contact current paths)

Input dataCoil side

Nominal input voltage UN 24 V DC

Input voltage range 20.2 V DC ... 33.6 V DC (20 °C)

Nominal voltage (plugged-in electromechanical relay) 24 V DC

Drive and function monostable

Drive (polarity) polarized

Typical input current at UN 18 mA

Input power dissipation for UN 0.43 W

Typical response time 8 ms

Typical release time 10 ms

Protective circuit Reverse polarity protection; Polarity protection diode

Freewheeling diode; Freewheeling diode

Operating voltage display Yellow LED

Output dataSwitching

Contact switching type 2 N/O contacts

Type of switch contact Single contact

Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RSC-24DC/ 1-1/ACT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.