


INDUSTRIAL COMPONENT DATA

PLC-APT-UI-OUT 2906921 PHOENIX CONTACT Extension module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-APT-UI-OUT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-APT-UI-OUT
Catalog number	2906921
Category	PLC analogue I/O-module
Minimum order	1 Pcs
Document ID	EO-C6BCAA95B5
Generated	2026-08-04

Product Overview

Extension module

Analog output module for PLC logic modules (generation 2 only), single-channel, signal type (4 ... 20 mA, 0 ... 20 mA, 0 ... 10 V, 2 ... 10 V) configurable via DIP switch, push-in connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2906921

Packing unit 1 pc

Catalog page Page 431 (C-5-2017)

GTIN 4055626155524

Weight per Piece (excluding packing) 50.300 g

Custom tariff number 85389099

Country of origin DE (Germany)

Dimensions

Width 6.2 mm

Height 80 mm

Depth 86 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Supply

Rated control circuit supply voltage US 24 V DC

Rated control supply voltage range with reference to US 0.8 ... 1.1

Rated control supply current IS ≤ 28 mA

Type of protection Reverse polarity protection

Surge protection

Operating voltage display Green LED

Indication Red LED

Input data

Input name Digital input

Output data

Output name Analog voltage output

Voltage output signal 0 V ... 10 V

2 V ... 10 V

Maximum output voltage 12.3 V

Ripple < 20 mVPP

Load/output load voltage output 10 kΩ

Output protection

Surge voltage protection > 33 V

Maximum transmission error 1 %

Output name Analog output for current

Current output signal 0 mA ... 20 mA

4 mA ... 20 mA

Maximum output current 24.6 mA

Load/output load current output 500 Ω (20 mA)

Output protection

Surge voltage protection > 33 V

Maximum transmission error 1 %

General

Operating mode 100% operating factor

Degree of protection IP20

Mounting position any

Assembly instructions In rows with zero spacing

Connection data

Connection method Push-in connection

Stripping length 8 mm

Conductor cross section solid 0.14 mm² ... 2.5 mm²

Conductor cross se...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-APT-UI-OUT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.