

INDUSTRIAL COMPONENT DATA

PLC-BPT-125DC/21 2904590 PHOENIX CONTACT Relay base

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-BPT-125DC/21



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-BPT-125DC/21
Catalog number	2904590
Category	Relay socket
Minimum order	10 Pcs
Document ID	EO-4773340EFE
Generated	2026-08-05

Product Overview

Relay base

6.2 mm PLC base terminal block with push-in connection, without relay or solid-state relay equipment, for mounting on NS 35/7.5 rail, 1 switched contact, input voltage 125 V DC

6.2 mm PLC basic terminal block with Push-in connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 125 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Technical dataNotesUtilization restriction

EMC note EMC: class A product, see manufacturer's declaration in the download area

Product propertiesProduct type Relay socket

Product family PLC-INTERFACE

Application Universal

Operating mode 100% operating factor

Data management status

Article revision 02

Electrical propertiesProtective circuit Damping diode, polarity protection diode

Input dataNominal input voltage UN 125 V DC

The nominal voltage of the plug-on electromechanical relay or solid-state relay (see necessary accessories) deviates from the nominal input voltage of the base with integrated upstream circuit

Protective circuit Freewheeling diode

Nominal input voltage UN 125 V DC

The nominal voltage of the plug-on electromechanical relay or solid-state relay (see necessary accessories) deviates from the nominal input voltage of the base with integrated upstream circuit

Connection dataConnection method Push-in connection

Stripping length 10 mm

Conductor cross section rigid 0.14 mm² ... 2.5 mm²

Conductor cross section flexible 0.14 mm² ... 2.5 mm²

0.2 mm² ... 2.5 mm² (Single ferrule)

2x 0.5 mm² ... 1 mm² (TWIN ferrule)

Conductor cross section AWG 26 ... 14

SignalingStatus display LED

DimensionsWidth 6.2 mm

Height 80 mm

Depth 94 mm

Material specificationsColor gray (RAL 7042)

Flammability rating according to UL 94 V0 (Housing)

ApprovalsCE

Certificate CE-compliant

UKCA

Certificate UKCA-compliant

Shipbuilding approval

Certificate TAE0000196

Corrosive gas test

Identification ISA...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-BPT-125DC/21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.