

INDUSTRIAL COMPONENT DATA

PLC-BPT- 5DC/21 2900443 PHOENIX CONTACT Relay base

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-BPT-5DC/21



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-BPT-5DC/21
Catalog number	2900443
Category	Relay socket
Minimum order	10 Pcs
Document ID	EO-1AC07470AA
Generated	2026-08-05

Product Overview

Relay base

6.2 mm PLC base terminal block with push-in connection, without relay or solid-state relay equipment, for mounting on NS 35/7.5 rail, 1 switched contact, input voltage 5 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data

Orderkey 2900443

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4046356507585

Weight per Piece (excluding packing) 27.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 80 mm

Depth 94 mm

Input data

Nominal input voltage UN 5 V DC

Status display LED

Protective circuit Damping diode, polarity protection diode

Damping diode

Connection data, input side

Connection name Input side

Connection method Push-in connection

Stripping length 10 mm

Conductor cross section solid 0.14 mm² ... 2.5 mm²Conductor cross section flexible 0.14 mm² ... 2.5 mm²0.2 mm² ... 2.5 mm² ()2x 0.5 mm² ... 1 mm² ()

Conductor cross section AWG 26 ... 14

Connection data, output side

Connection name Output side

Connection method Push-in connection

Stripping length 10 mm

Conductor cross section solid 0.14 mm² ... 2.5 mm²Conductor cross section flexible 0.14 mm² ... 2.5 mm²0.2 mm² ... 2.5 mm² ()2x 0.5 mm² ... 1 mm² ()

Conductor cross section AWG 26 ... 14

General

Note Separating plate PLC-ATP must be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or FBST 500....

Protective circuit Damping diode, polarity protection diode

Color green

Operating mode 100% operating factor

Mounting position any

Standards and Regulations

Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-BPT-5DC/21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.