

INDUSTRIAL COMPONENT DATA

PLC-BSC- 12DC/ 1IC/ACT 1090867 PHOENIX CONTACT 14 mm PLC basic terminal block for high switch-on currents wi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-BSC- 12DC/ 1IC/ACT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-BSC- 12DC/ 1IC/ACT
Catalog number	1090867
Category	Relay socket
Minimum order	10 Pcs
Document ID	EO-BE956AD793
Generated	2026-07-29

Product Overview

14 mm PLC basic terminal block for high switch-on currents with screw connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, with load return line connection (BB), 1 N/O contact, input voltage 12 V DC

14 mm PLC base terminal block for high clamping currents with screw connection, without relay or solid-state relay equipment, for mounting on NS 35/7.5 rail, with load return line (BB) connection, 1 closing contact, input voltage 12 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 1090867

Packing unit 1 pc

GTIN 4055626901381

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

Drawings

Dimensions

Input data

General

[Connection data 2](#)

[Environmental Product Compliance](#)

[Note](#)

[Ambient conditions](#)

[Output data](#)

[Connection data](#)

[Standards and Regulations](#)

[Classifications](#)

[Drawings](#)

[Circuit diagram](#)

[Back to top](#)[Note](#)

Note Separating plate PLC-ATP must be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules.

The PLC-ATP separating plate should be installed for safe isolation between adjacent modules

The PLC-ATP separating plate is required at the start and end of every PLC terminal strip.

The system installer must ensure the touch protection of the product (at voltages > 25 V AC/60 V DC). The product is a built-in device without protection against direct contact.

[Back to top](#)[Dimensions](#)

Width 14 mm

Height 80 mm

Depth 94 mm

[Back to top](#)[Ambient conditions](#)

Ambient temperature (operation) -40 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Maximum altitude ≤ 2000 m

Degree of protection IP20

≥ IP54 (Installation location)

[Back to top](#)[Input data](#)

Nominal input voltage UN 12 V DC

Protective circuit Damping diode

Polarity protection diode

[Back to top](#)[Output data](#)

Compatible components Miniature relay, 2904475 REL-MR- 12DC/1IC, 1081616 REL-MR- 12DC/1ICT

[Back to top](#)[General](#)

Color gray

Operating mode 100% operating factor

Mounting pos...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-BSC- 12DC/ 1IC/ACT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.