

INDUSTRIAL COMPONENT DATA

PLC-BSC-230UC/ 1/SEN 2966087 PHOENIX CONTACT Relay base

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-BSC-230UC/ 1/SEN



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-BSC-230UC/ 1/SEN
Catalog number	2966087
Category	Relay socket
Minimum order	10 Pcs
Document ID	EO-C89E2670CB
Generated	2026-08-02

Product Overview

Relay base

6.2 mm PLC base terminal block for input functions with screw connection, without relay or solid-state relay equipment, for mounting on NS 35/7.5 rail, with sensor supply voltage distribution (BB), 1 closing contact, input voltage 230 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Technical dataNotesUtilization restriction

EMC note EMC: class A product, see manufacturer's declaration in the download area

Product propertiesProduct type Relay socket

Product family PLC-INTERFACE

Application Input function

Operating mode 100% operating factor

Data management status

Article revision 11

Insulation characteristics

Pollution degree 3

Electrical propertiesProtective circuit Bridge rectifier

Input dataNominal input voltage UN 230 V AC/DC

The nominal voltage of the plug-on electromechanical relay or solid-state relay (see necessary accessories) deviates from

the nominal input voltage of the base with integrated upstream circuit

Protective circuit Bridge rectifier

Nominal input voltage UN 230 V AC/DC

The nominal voltage of the plug-on electromechanical relay or solid-state relay (see necessary accessories) deviates from the nominal input voltage of the base with integrated upstream circuit

Connection dataConnection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section rigid 0.14 mm² ... 2.5 mm²

Conductor cross section flexible 0.14 mm² ... 2.5 mm²

0.2 mm² ... 2.5 mm² (Single ferrule)

2x 0.5 mm² ... 1.5 mm² (TWIN ferrule)

Conductor cross section AWG 26 ... 14

Tightening torque 0.6 Nm ... 0.8 Nm

SignalingStatus display LED

DimensionsWidth 6.2 mm

Height 80 mm

Depth 94 mm

Material specificationsColor gray (RAL 7042)

Flammability rating according to UL 94 V0 (Housing)

Environmental and real-life conditionsAmbient conditions

Ambient temp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-BSC-230UC/ 1/SEN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.