

INDUSTRIAL COMPONENT DATA

PLC-BSC- 24UC/21-21 2967028 PHOENIX CONTACT Relay base

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-BSC-24UC/21-21



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-BSC-24UC/21-21
Catalog number	2967028
Category	Relay socket
Minimum order	1 Pcs
Document ID	EO-6585A1D0CF
Generated	2026-08-05

Product Overview

Relay base

14 mm PLC base terminal block with screw connection, without relay or solid-state relay equipment, for mounting on NS 35/7.5 rail, 2 switched contacts, input voltage 24 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Relays**

Additional Product Information

Key Commercial Data

Orderkey 2967028

Packing unit 10 pc

GTIN 4017918156466

Weight per Piece (excluding packing) 55.600 g

Custom tariff number 85369010

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 14 mm

Height 80 mm

Depth 94 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Input data

Nominal input voltage UN 24 V AC/DC

Status display LED

Protective circuit Bridge rectifier

Output data

Compatible components Miniature relay, REL-MR-24DC/21-21AU, REL-MR-24DC/21-21

Connection data, input side

Connection name Input side

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.14 mm² ... 2.5 mm²Conductor cross section flexible 0.14 mm² ... 2.5 mm²0.2 mm² ... 2.5 mm² ()2x 0.5 mm² ... 1.5 mm² ()

Conductor cross section AWG 26 ... 14

Connection data, output side

Connection name Output side

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.14 mm² ... 2.5 mm²Conductor cross section flexible 0.14 mm² ... 2.5 mm²0.2 mm² ... 2.5 mm² ()2x 0.5 mm² ... 1.5 mm² ()

Conductor cross section AWG 26 ... 14

General

Color green

Operating mode 100% operating factor

Mounting position any

Assembly instructions In rows with zero spacing

Standards and Regulations

Connection in acc. with standard CUL

Flammability rati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-BSC-24UC/21-21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.