

INDUSTRIAL COMPONENT DATA

PLC-OSC-120UC/ 48DC/100/C1D2 5603263 PHOENIX CONTACT Optocoupler

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-OSC-120UC/ 48DC/100/C1D2



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-OSC-120UC/ 48DC/100/C1D2
Catalog number	5603263
Category	Optocoupler
Minimum order	1 Pcs
Document ID	EO-FE176CF652
Generated	2026-08-02

Product Overview

Optocoupler

PLC-INTERFACE, consisting of a rail-mounted base terminal block with screw connection and plug-in miniature solid-state relay, input: 120 V AC/110 V DC, output: 3-48 V DC/100 mA, UL/cUL: approved for use in the Ex zone class I, div. 2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Relays**

Additional Product Information

Key Commercial Data

Orderkey 5603263

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 459 (C-5-2017)

GTIN 4046356683388

Weight per Piece (excluding packing) 33.330 g

Custom tariff number 85364900

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 80 mm
Depth 94 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Input data
Nominal input voltage UN 120 V AC
110 V DC
Input voltage range in reference to UN 0.9 ... 1.1
Input voltage range 108 V AC ... 132 V AC
99 V DC ... 121 V DC
Switching threshold "0" signal in reference to UN ≤ 0.3
Switching threshold "1" signal in reference to UN ≥ 0.9
Typical input current at UN 3.5 mA
Typical response time 3 ms (at UN)
Typical turn-off time 4 ms (at UN)
Operating voltage display Yellow LED
Type of protection Bridge rectifier
Protective circuit/component Bridge rectifier
Transmission frequency 10 Hz
Power dissipation for nominal condition 0.42 W
Output data
Output voltage range 3 V DC ... 48 V DC
Limiting continuous current 100 mA
Voltage drop at max. limiting continuous current ≤ 1 V
Output circuit 2-wire, floating
Type of protection Reverse polarity protection
Surge protection
Protective circuit/component Polarity protection diode
Connection data, input side
Connection name Input side
Connection method Screw connection
Strippin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-OSC-120UC/ 48DC/100/C1D2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.