

INDUSTRIAL COMPONENT DATA

PLC-OSC- 24DC/ 24DC/ 2/C1D2 5603260 PHOENIX CONTACT Optocoupler

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-OSC-24DC/ 24DC/ 2/C1D2



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-OSC-24DC/ 24DC/ 2/C1D2
Catalog number	5603260
Category	Optocoupler
Minimum order	1 Pcs
Document ID	EO-D1FE723E72
Generated	2026-07-29

Product Overview

Optocoupler

PLC-INTERFACE, consisting of a base terminal block for mounting on a rail with screw connection and plug-in miniature solid-state relay, input: 24VDC, output: 3 ... 33VDC/3A, UL/CUL: approved for use in Ex zone class I, div. 2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 5603260

Packing unit 10 pc

Catalog page Page 459 (C-5-2017)

GTIN 4046356686129

Weight per Piece (excluding packing) 38.000 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 80 mm

Depth 94 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Input data

Nominal input voltage UN 24 V DC

Input voltage range in reference to UN 0.8 ... 1.2

Input voltage range 19.2 V DC ... 28.8 V DC

Switching threshold "0" signal in reference to UN ≤ 0.4

Switching threshold "1" signal in reference to UN ≥ 0.8

Typical input current at UN 8.5 mA

Typical response time 20 μ s (at UN)

Typical turn-off time 300 μ s (at UN)

Operating voltage display Yellow LED

Type of protection Reverse polarity protection

Free-wheeling diode

Protective circuit/component Polarity protection diode

Damping diode

Transmission frequency 300 Hz

Power dissipation for nominal condition 0.2 W

Output data

Output voltage range 3 V DC ... 33 V DC

Limiting continuous current 3 A

Maximum inrush current 15 A (10 ms)

Voltage drop at max. limiting continuous current ≤ 200 mV

Output circuit 2-wire, floating

Type of protection Reverse polarity protection

Surge protection

Protective circuit/component Polarity protection diode

Connection data, input side

Connection name Input side

Connection meth...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-OSC-24DC/ 24DC/ 2/C1D2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.