

INDUSTRIAL COMPONENT DATA

PLC-OPT- 24DC/230AC/1 2900369 PHOENIX CONTACT

Solid-state relay module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-OPT-24DC/230AC/1



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-OPT-24DC/230AC/1
Catalog number	2900369
Category	Optocoupler
Minimum order	1 Pcs
Document ID	EO-B455B90257
Generated	2026-07-31

Product Overview

Solid-state relay module

PLC-INTERFACE, PLC-BPT.../21 base terminal composite with push-in connection and plug-in miniature solid state relay, for NS rail mounting 35/7.5, 1 closing contact, input: 24 V DC, output: 24-253 V AC/ 0.75 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Relays**

Additional Product Information

Key Commercial Data

Orderkey 2900369

Packing unit 10 pc

Catalog page Page 377 (C-5-2017)

GTIN 4046356506885

Weight per Piece (excluding packing) 31.270 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 80 mm

Depth 94 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C

Ambient temperature (storage/transport) -25 °C ... 70 °C

Input data

Nominal input voltage UN 24 V DC

Input voltage range in reference to UN 0.8 ... 1.2

Input voltage range 19.2 V DC ... 28.8 V DC

Switching threshold "0" signal in reference to UN ≤ 0.25

Switching threshold "1" signal in reference to UN ≥ 0.8

Typical input current at UN 8 mA

Typical response time 10 ms (at UN)

Typical turn-off time 10 ms (at UN)

Operating voltage display Yellow LED

Type of protection Reverse polarity protection

Free-wheeling diode

Protective circuit/component Polarity protection diode

Damping diode

Transmission frequency 10 Hz

Power dissipation for nominal condition 0.19 W

Output data

Output voltage range 24 V AC ... 253 V AC

Limiting continuous current 0.75 A (see derating curve)

Maximum inrush current 30 A (10 ms)

Min. load current 10 mA

Leakage current < 1 mA (in off state)

Max. load value 4.5 A2s

Voltage drop at max. limiting continuous current < 1 V

Output circuit 2-wire, floating

Type of protection RCV circuit

Connection data 1

Connection name Input side

Connec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-OPT-24DC/230AC/1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.