

INDUSTRIAL COMPONENT DATA

PLC-OSC- 60DC/ 24DC/ 2 2967468 PHOENIX CONTACT

Solid-state relay module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-OSC-60DC/ 24DC/ 2



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-OSC-60DC/ 24DC/ 2
Catalog number	2967468
Category	Optocoupler
Minimum order	1 Pcs
Document ID	EO-AA5584BB09
Generated	2026-08-01

Product Overview

Solid-state relay module

PLC-INTERFACE, consisting of PLC-BSC.../21 base terminal block with screw connection and plug-in miniature solid-state relay, for NS 35/7.5 rail mounting, 1 closing contact, input: 60 V DC, output: 3-33 V DC/ 3 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2967468

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 377 (C-5-2017)

GTIN 4017918165840

Weight per Piece (excluding packing) 32.260 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 80 mm
Depth 94 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 60 °C
Ambient temperature (storage/transport) -25 °C ... 70 °C
Input data
Nominal input voltage UN 60 V DC
Input voltage range in reference to UN 0.8 ... 1.2
Input voltage range 48 V DC ... 72 V DC
Switching threshold "0" signal in reference to UN ≤ 0.3
Switching threshold "1" signal in reference to UN ≥ 0.8
Typical input current at UN 5 mA
Typical response time 40 μ s (at UN)
Typical turn-off time 500 μ s (at UN)
Operating voltage display Yellow LED
Type of protection Reverse polarity protection
Free-wheeling diode
Protective circuit/component Polarity protection diode
Damping diode
Transmission frequency 100 Hz
Power dissipation for nominal condition 0.3 W
Output data
Output voltage range 3 V DC ... 33 V DC
Limiting continuous current 3 A (see derating curve)
Maximum inrush current 15 A (10 ms)
Voltage drop at max. limiting continuous current ≤ 200 mV
Output circuit 2-wire, floating
Type of protection Reverse polarity protection
Surge protection
Protective circuit/component Polarity protection diode
Connection data 1
C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-OSC-60DC/ 24DC/ 2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.