

## INDUSTRIAL COMPONENT DATA

# PLC-RPT-230UC/21 2900305 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RPT-230UC/21



|                 |                  |
|-----------------|------------------|
| Manufacturer    | PHOENIX CONTACT  |
| MPN / Reference | PLC-RPT-230UC/21 |
| Catalog number  | 2900305          |
| Category        | Switching relay  |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-1A13CE4817    |
| Generated       | 2026-07-29       |

## Product Overview

### Relay Module

PLC-INTERFACE, consists of a PLC-BPT.../21 base terminal block with Push-in connection and plug-in miniature relay with power contact, for mounting on NS 35/7.5 symmetrical rail, 1 reverse contact, input voltage 230 V AC/220 V DC

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Industrial Relays

## Additional Product Information

### Key Commercial Data

Orderkey 2900305

Packing unit 10 pc

Catalog page Page 372 (C-5-2017)

GTIN 4046356507004

Weight per Piece (excluding packing) 31.270 g

Custom tariff number 85364900

Country of origin DE (Germany)

### Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Note Separating plate PLC-ATP must be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or FBST 500....

### Dimensions

Width 6.2 mm  
Height 80 mm  
Depth 94 mm  
Ambient conditions  
Ambient temperature (operation) -40 °C ... 55 °C  
Ambient temperature (storage/transport) -40 °C ... 85 °C  
Coil side  
Nominal input voltage UN 230 V AC  
220 V DC  
Typical input current at UN 3.2 mA (at UN= 230 V AC)  
3 mA (at UN= 220 V DC)  
Typical response time 7 ms  
Typical release time 15 ms  
Protective circuit Bridge rectifier Bridge rectifier  
Operating voltage display Yellow LED  
Power dissipation for nominal condition 0.74 W  
Contact side  
Contact type 1 PDT  
Type of switch contact Single contact  
Contact material AgSnO  
Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)  
Minimum switching voltage 5 V (at 100 mA)  
Min. switching current 10 mA (at 12 V)  
Maximum inrush current 10 A...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RPT-230UC/21 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.