

INDUSTRIAL COMPONENT DATA

PLC-RSC-230UC/21-21 2967099 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RSC-230UC/21-21



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RSC-230UC/21-21
Catalog number	2967099
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-BF18540DAF
Generated	2026-08-04

Product Overview

Relay Module

PLC interface, consisting of PLC-BSC.../21 base terminal block with screw connection and plug-in miniature relay with power contact, for installation on NS 35/7.5 rail, 2 switched contacts, input voltage 230 V AC/220 V DC

PLC-INTERFACE, consisting of basic terminal block PLC-BSC.../21 with screw connection and plug-in miniature relay with power contact, for assembly on DIN rail NS 35/7,5, 2 changeover contacts, input voltage 230 V AC/220 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Technical dataProduct propertiesProduct type Relay Module

Product family PLC-INTERFACE

Application Universal

Operating mode 100% operating factor

Mechanical service life 3x 10⁷cycles

Data management status

Date of last data management 07.08.2024

Article revision 11

Insulation characteristics

Insulation Safe isolation: Control side / contact side

Overvoltage category III

Pollution degree 3

Electrical properties Maximum power dissipation for nominal condition 1.04 W

Test voltage (Winding/contact) 4 kV AC (50 Hz, 1 min., winding/contact)

Test voltage (Changeover contact/changeover contact) 2.5 kV AC (50 Hz, 1 min., changeover contact/changeover contact)

Rated surge voltage 6 kV

Input data Coil side

Nominal input voltage UN 230 V AC

220 V DC

Input voltage range 179.4 V AC ... 264.5 V AC (20 °C)

171.6 V DC ... 264 V DC (20 °C)

Nominal voltage (plugged-in electromechanical relay) 110 V DC

Drive and function monostable

Drive (polarity) polarized

Typical input current at UN 4.5 mA (at UN= 230 V AC)

4.3 mA (at UN= 220 V DC)

Typical response time 7 ms

Typical release time 10 ms

Protective circuit Bridge rectifier; Bridge rectifier

Operating voltage display Yellow LED

Output data Switching

Contact switching type 2 changeover contacts

Type of switch contact Single contact

Contact material AgNi

Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential br...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RSC-230UC/21-21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.