

INDUSTRIAL COMPONENT DATA

PLC-RSC- 24DC/21HC 2967620 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RSC-24DC/21HC



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RSC-24DC/21HC
Catalog number	2967620
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-D7430A173A
Generated	2026-08-01

Product Overview

Relay Module

PLC-INTERFACE for high constant currents, consisting of PLC-BSC.../21 HC base terminal block with screw connection and plug-in miniature relay, for DIN rail mounting NS 35/7.5, direct current limit up to 10 A, 1 switch, input voltage 24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data

Orderkey 2967620

Packing unit 10 pc

Catalog page Page 387 (C-5-2017)

GTIN 4017918171643

Weight per Piece (excluding packing) 74.210 g

Custom tariff number 85364900

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 14 mm

Height 80 mm

Depth 94 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Coil side

Nominal input voltage UN 24 V DC

Typical input current at UN 18 mA

Typical response time 8 ms

Typical release time 10 ms

Protective circuit Reverse polarity protection Polarity protection diode

Free-wheeling diode Damping diode

Operating voltage display Yellow LED

Power dissipation for nominal condition 0.43 W

Contact side

Contact type 1 PDT

Type of switch contact Single contact

Contact material AgNi

Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)

Minimum switching voltage 12 V DC (at 10 mA)

Min. switching current 10 mA (at 12 V)

Maximum inrush current 30 A (300 ms)

Limiting continuous current 10 A

6 A (value applies to connections 12. If connections 12 are bridged, the normal value applies.)

Interrupting rating (ohmic load) max. 240 W (at 24 V DC)

58 W (at 48 V DC)

48 W....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RSC-24DC/21HC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.