

INDUSTRIAL COMPONENT DATA

PLC-RPT-230UC/21HC/MS 2910534 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RPT-230UC/21HC/MS



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RPT-230UC/21HC/MS
Catalog number	2910534
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-D49C750962
Generated	2026-07-29

Product Overview

Relay Module

PLC-INTERFACE, consisting of socket relay and relay with plug-in power contact with manual activation, integrated status LED, push-in connection, 1 switch, Rectifier bridge, Input voltage: 230 VAC / 220 VDC

PLC-INTERFACE, consisting of a relay base and pluggable power contact relay with manual operation, integrated status LED, Push-in connection, 1 changeover contact, Bridge rectifier, Input voltage: 230 V AC / 220 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Technical dataProduct propertiesProduct type Relay Module

Product family PLC-INTERFACE

Application Palm switch

High continuous currents

Operating mode 100% operating factor

Mechanical service life 5x 10⁶cycles

Data management status

Date of last data management 09.07.2024

Article revision 03

Insulation characteristics

Insulation Safe isolation, reinforced insulation

Overvoltage category III

Pollution degree 2

Electrical properties Maximum power dissipation for nominal condition 0.22 W

Test voltage (Winding/contact) 4 kVrms(50 Hz, 1 min., winding/contact)

Rated insulation voltage 250 V AC

Rated surge voltage 6 kV

Input data Coil side

Nominal input voltage UN 230 V AC

220 V DC

Input voltage range 207 V AC ... 264.5 V AC (20 °C)

209 V DC ... 264 V DC (20 °C)

Nominal voltage (plugged-in electromechanical relay) 110 V DC

Drive and function monostable

Drive (polarity) polarized

Typical input current at UN 5 mA

Typical response time 6 ms (220 V DC)

3 ms ... 15 ms (230 V AC)

Typical release time 8 ms (220 V DC)

Typical release time range 3 ms ... 15 ms (230 V AC)

Protective circuit Bridge rectifier; Bridge rectifier

Operating voltage display Yellow LED

Output data Switching

Contact switching type 1 changeover contact

Type of switch contact Single contact

Contact material AgNi

Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RPT-230UC/21HC/MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.