

INDUSTRIAL COMPONENT DATA

PLC-RPT- 24UC/21HC/MS 2910531 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RPT-24UC/21HC/MS



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RPT-24UC/21HC/MS
Catalog number	2910531
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-EF37FB64FB
Generated	2026-08-02

Product Overview

Relay Module

PLC-INTERFACE, consisting of socket relay and relay with plug-in power contact with manual activation, integrated status LED, push-in connection, 1 switch, Rectifier bridge, Input voltage: 24 V AC/DC

PLC-INTERFACE, consisting of a relay base and pluggable power contact relay with manual operation, integrated status LED, Push-in connection, 1 changeover contact, Bridge rectifier, Input voltage: 24 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Technical dataProduct propertiesProduct type Relay Module

Product family PLC-INTERFACE

Application Palm switch

High continuous currents

Operating mode 100% operating factor

Mechanical service life 5x 106cycles

Data management status

Date of last data management 08.07.2024

Article revision 03

Insulation characteristics

Insulation Safe isolation, reinforced insulation

Overvoltage category III

Pollution degree 2

Electrical properties Maximum power dissipation for nominal condition 0.44 W

Test voltage (Winding/contact) 4 kVrms(50 Hz, 1 min., winding/contact)

Rated insulation voltage 250 V AC

Rated surge voltage 6 kV

Input data Coil side

Nominal input voltage UN 24 V AC/DC

Input voltage range 20.6 V AC/DC ... 33.6 V AC/DC (20 °C)

Nominal voltage (plugged-in electromechanical relay) 24 V DC

Drive and function monostable

Drive (polarity) polarized

Typical input current at UN 18 mA

Typical response time 3 ms ... 15 ms

Typical release time range 3 ms ... 15 ms

Protective circuit Bridge rectifier; Bridge rectifier

Operating voltage display Yellow LED

Output data Switching

Contact switching type 1 changeover contact

Type of switch contact Single contact

Contact material AgNi

Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)

Minimum switching voltage 12 V (10 mA)

Limiting continu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RPT-24UC/21HC/MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.