

INDUSTRIAL COMPONENT DATA

PLC-RSC-120UC/21HC/EX 2909520 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RSC-120UC/21HC/EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RSC-120UC/21HC/EX
Catalog number	2909520
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-E2D8F2747D
Generated	2026-08-05

Product Overview

Relay Module

PLC-INTERFACE, consisting of a 14 mm rail-mounted base terminal block with screw connection and plug-in relay with 10 A power contact, 1 switched contact, input voltage 120 V AC/110 V DC. Approved according to ATEX/IECEEx (zone 2) and Ex zone class I, div. 2.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2909520

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 459 (C-5-2017)

GTIN 4055626363486

Weight per Piece (excluding packing) 70.630 g

Custom tariff number 85364900

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 14 mm

Height 80 mm

Depth 94 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C (UL)

-40 °C ... 60 °C (ATEX / IECEx)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Coil side

Nominal input voltage UN 120 V AC

110 V DC

Typical input current at UN 4.5 mA

Typical response time 7 ms

Typical release time 10 ms

Protective circuit Bridge rectifier Bridge rectifier

Operating voltage display Yellow LED

Power dissipation for nominal condition 0.54 W

Contact side

Contact type 1 PDT

Type of switch contact Single contact

Contact material AgNi

Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)

Minimum switching voltage 12 V (at 10 mA)

Min. switching current 10 mA (at 12 V)

Maximum inrush current 30 A (300 ms)

Limiting continuous current 10 A

6 A (value applies to connections 12. If connections 12 are bridged, the normal value applies.)

Interrupting rating (ohm...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RSC-120UC/21HC/EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.