

INDUSTRIAL COMPONENT DATA

PLC-RSC-230UC/21-21/MS 2910506 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RSC-230UC/21-21/MS



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RSC-230UC/21-21/MS
Catalog number	2910506
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-4F2CB30800
Generated	2026-08-03

Product Overview

Relay Module

PLC-INTERFACE, consisting of socket relay and relay with plug-in power contact with manual activation, integrated status LED, screw connection, 2 switched contacts, Rectifier bridge, Input voltage: 230 VAC / 220 VDC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Relays**

Additional Product Information

Key Commercial Data

Orderkey 2910506

Packing unit 10 pc

Note Made to Order (non-returnable)

GTIN 4055626486611

Weight per Piece (excluding packing) 67.000 g

Custom tariff number 85364900

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 14 mm

Height 80 mm

Depth 104 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 85 °C

Coil side

Nominal input voltage UN 230 V AC

220 V DC

Typical input current at UN 5 mA

Typical response time 6 ms (220 V DC)

3 ms ... 15 ms (230 V AC)

Typical release time 10 ms (220 V DC)

Typical release time range 3 ms ... 15 ms (230 V AC)

Protective circuit Bridge rectifier Bridge rectifier

Operating voltage display Yellow LED

Contact side

Contact type 2 PDT

Type of switch contact Single contact

Contact material AgNi

Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)

Minimum switching voltage 12 V (10 mA)

Min. switching current 10 mA (12 V)

Maximum inrush current 12 A (20 ms)

Limiting continuous current 6 A

Interrupting rating (ohmic load) max. 192 W (24 V DC)

62 W (48 V DC)

42 W (60 V DC)

55 W (110 V DC)

66 W (220 V DC)

2000 VA (250 V AC)

Switching capacity 1 A (24 V, DC13)

1.5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RSC-230UC/21-21/MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.