

INDUSTRIAL COMPONENT DATA

PLC-OPT-230UC/ 48DC/100/SEN 2900361 PHOENIX CONTACT PLC-INTERFACE for input functions, consisting of PLC-BPT..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-OPT-230UC/ 48DC/100/SEN



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-OPT-230UC/ 48DC/100/SEN
Catalog number	2900361
Category	Optocoupler
Minimum order	1 Pcs
Document ID	EO-7FEB935B4C
Generated	2026-08-02

Product Overview

PLC-INTERFACE for input functions, consisting of PLC-BPT.../SEN basic terminal block with push-in connection and plug-in miniature solid-state relay, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input: 230 V AC/220 V DC, output: 3 - 48 V DC/100 mA

PLC-INTERFACE for input functions, consisting of PLC-BPT.../SEN base terminal block with push-in connection and plug-in miniature solid-state relay, for NS 35/7.5 rail mounting, 1 closing contact, input: 230 V AC/220 V DC, output: 3-48 V DC/100 mA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Dimensions

Width 6.2 mm

Height 80 mm

Depth 94 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C

Ambient temperature (storage/transport) -25 °C ... 70 °C

Input data

Nominal input voltage UN 230 V AC (220 V DC)

220 V DC

Input voltage range in reference to UN 0.8 ... 1.1
Switching threshold "0" signal in reference to UN ≤ 0.3
Switching threshold "1" signal in reference to UN ≥ 0.8
Typical input current at UN 3.5 mA
Typical response time 3 ms (at UN)
Typical turn-off time 5 ms (at UN)
Operating voltage display Yellow LED
Type of protection Bridge rectifier
Protective circuit/component Bridge rectifier
Transmission frequency 10 Hz
Output data
Output voltage range 3 V DC ... 48 V DC
Limiting continuous current 100 mA
Voltage drop at max. limiting continuous current ≤ 1 V
Output circuit 2-wire, floating
Type of protection Protection against polarity reversal
Surge protection
Protective circuit/component Polarity protection diode
Connection data, input side
Connection name Input side
Connection method Push-in connection
Stripping length 8 mm
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section AWG 26 ... 14
General
Test voltage input/output 2.5 kV (50 Hz, 1 min.)
Mounting position any
Assembly instructions In rows with zero spacing
Operating mode 100% operating factor
Flammability rating according to UL 94 V0
Designation Standards/regulations
Standards/regulations IEC 60664
EN 50178
IEC....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-OPT-230UC/ 48DC/100/SEN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.