

INDUSTRIAL COMPONENT DATA

PLC-V8C/PT-24DC/SAM2 2907443 PHOENIX CONTACT Controller

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-V8C/PT-24DC/SAM2



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-V8C/PT-24DC/SAM2
Catalog number	2907443
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-F0486582F5
Generated	2026-08-02

Product Overview

Controller

Standalone PLC logic module, 2nd generation, with 16 I/O, pluggable into 8 digital or analogue PLC-INTERFACE terminals, not expandable, real-time clock, Micro-USB female connector, housing for memory module and Bluetooth adapter, push-in connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2907443

Packing unit 1 pc

Catalog page Page 428 (C-5-2017)

GTIN 4055626218182

Weight per Piece (excluding packing) 130.000 g

Custom tariff number 85371098

Country of origin DE (Germany)

Power supply

Supply voltage 24 V DC

Supply voltage range 19.2 V DC ... 26.4 V DC

Typical input current at UN 40 mA

Maximum input current at UN 160 mA
Protective circuit Reverse polarity protection
Surge protection
Status display Green LED
Input data (digital)
Number of inputs 8 (2 configurable as analog)
Description of the input EN 61131-2, type 3
Input voltage 24 V DC
Signal level "0" signal < 5 V
Signal level "1" signal > 11 V
Input current "0" signal < 1 mA
Input current "1" signal typ. 2.5 mA
Status display Yellow LED
Input data (analog)
Number of inputs 2 (IN6 and IN7 are configurable as analog)
Input voltage range 0 V ... 10 V
Input resistance > 3.5 k Ω
Input data (PLC-INTERFACE)
Number of inputs $\leq$ 8
Description of the input technical data depends on the PLC-INTERFACE terminal block used
Input voltage 19 V DC
Typical current consumption 4 mA
Input resistance < 100 m Ω
Output data
Number of outputs $\leq$ 8
Nominal output voltage 24 V DC
Nominal current 9 mA
General
Realtime clock accuracy ± 2 s/d
Realtime clock buffer time 96 h (Capacitor)
Color gray
Mounting position any
Assembly instructions can be plugged onto 8 x PLC-INTERFACE terminal blocks
Operating mode 100% operating factor
Degree of protection IP20
Connection data (supply and digital inputs)
Connection met...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-V8C/PT-24DC/SAM2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.